## CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

MON. NO. 4 = 35578 = 3547

Scanned 3/9/01 MPM

Alignment Corner of Section 3	Township 28 Range 22 4 P.M.
STATE OF MINNESOTA, County of Ramsey	
At the corner location shown on the sketch	
On 5-19-99 found # 20"	C. I's (marked "5t. Paul")
dele	
lest monument as sound lowered m	nonument removed monument (explain)
On 6-24-99 placed # 2	O" C.I's (marked St. Paul)
SKETCH OF REFERE	NCE TIES
AWAIL	
SPEK in well in the	
NA4 Sin walk joint (#10)	
355 m	
THERE WARD	
7570-	MATON DO BY DE DK3
to tack	#6 179-59-20 NM WALK
(** タ)	
	Ho # 1
	1548
<b>*</b> /	
$\emptyset = C.I$	
OVER FOR INFO	
	st. sign to SP.P Vi ipk. 1
Statement of evidence relative to this corner is available	able from St. Paul Public Works Dept., Survey Division
I hereby certify that this document and the data contained	Office of The County Recorder, County of Ramsey
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.	I hereby certify that this document was filed in the county
	Recorders office atm. on theday of
ECNATURE DATE	
Registration No. County Surveyor	County Decorder
Professional Engineer	County Recorder
Chief Surveyor, City of St. Paul	By Deputy  DOCUMENT NUMBER
Le comer surveyor, city or st. rem	DOCUMENT ITOMOGN

PK			235,63	
· PK	(3)	3-59-28	28,05	
3551 = C.Z	- 4 (84°)	44"	757.93	
35-46 = C.I.		03'33"	30.19	
3548 = C.Z.	6 9/0-		136.25	
3549 = C.Z.			184.67	
3550 = C.Z	- 11 90-0	0-00	545.55	

$$3547 = C.I. 8$$
 $0^{\circ}$ 
 $757.93$ 
 $3550 = C.I. 11$ 
 $354-14-37$ 
 $213.88$ 
 $10$ 
 $259^{\circ}23'28''$ 
 $27.65$ 
 $10$ 
 $10^{\circ}$ 
 $10^$